

THERMO12 - Thermocouple Expansion Module



THERMO12 - 12 channel K type thermocouple module for temperature measurements

- 12 channels for separate thermocouple inputs
- Serial data connection for data output and configuration
- Configurable CAN data output
- 4 status LEDs for Power, Status, CAN and Serial communication
- Stacking case, connects neatly with other Race Technology system components
- Integration with Race Technology components, aligned connectors, single power supply connector
- Reverse polarity protection with resettable fuses for all inputs



THERMO12 Configuration - v1.2.12

Input	Sampling Rate (seconds)	Map channel to	Serial output rate (Hz)	CAN output rate (Hz)	CAN address (Hex)	CAN RTR	Enabled / Disabled
01	0	Intake 1 Temperature T1	2500	Disabled	0x01020	Disabled	On
02	0	Inlet pre turbo 1 Temperature T2	2500	Disabled	0x01020	Disabled	On
03	0	Inlet pre turbo 2 Temperature T3	2500	Disabled	0x01020	Disabled	On
04	0	Inlet post turbo 1 Temperature T4	2500	Disabled	0x01020	Disabled	On
05	0	Inlet post turbo 2 Temperature T5	2500	Disabled	0x01020	Disabled	On
06	0	Inlet post intercooler 1 Temperature T6	2500	Disabled	0x01020	Disabled	On
07	0	Inlet post intercooler 2 Temperature T7	2500	Disabled	0x01020	Disabled	On
08	0	Water temp Temperature T8	2500	Disabled	0x01020	Disabled	On
09	0	Oil temp Temperature T9	2500	Disabled	0x01020	Disabled	On
10	0	Gearbox temp Temperature T10	2500	Disabled	0x01020	Disabled	On
11	0	Gearbox cool temp Temperature T11	2500	Disabled	0x01020	Disabled	On
12	0	Type 1 temp Temperature T12	2500	Disabled	0x01020	Disabled	On

CAN settings: CAN baud rate: 115200 Change CAN ID length: 20 Change Use default RT CAN addresses Generate CAN IDs

Communications: Serial Port 1: COM1 Serial Configuration Read Configuration

Supplied with complete software suite, including unit configuration software, live data monitoring and comprehensive data analysis program.

THERMO12 - Thermocouple Expansion Module

General	
Supply voltage	+5.5V to 24V
Power consumption	1W
Case construction	Die-cast aluminium
Dimensions	164 x 63 x 34mm
Mass	300g
IP rating	IP50
Operating temperature range	-40 to 70 °C
Mounting method	Cases stack to other RT products / Velcro / tie wraps
Outputs	RS232, CAN
CAN output	
Maximum baud rate	1 Mbit/s
Data rate	Configurable up to 20Hz per channel
Identifiers	Configurable addresses, 11 or 29 bit
RS232 (serial) connection	
Baud rate	Adjustable 4800-921600 baud
Data rate	Configurable up to 20Hz per channel
RS232 data format	RT format temperature channels
Thermocouple Inputs	
Sample rate	Variable up to 20Hz per channel
Type	K-type (grounded tip or floating)
Internal resolution	2mK
Resolution	24 bits
Typical accuracy at 25 °C ambient	0.5 degrees C
Hardware filter	RC digital low-pass
Maximum input range	-200 to +1350 degrees C

Race Technology Ltd (UK)

16 King Street, Eastwood, Nottingham, NG16 3DA

Tel: +44 (0)1773 537620

Fax: +44 (0)1773 537621

Email: sales@race-technology.com